

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-023051**

Version 1 / September 2014

**KRIMELTE**

Member of  **Wolf Group**



Page 1 of 2

---

**1. Unique identification code of the product-type:**

ETS NORD Firestop Silicone

---

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

Batch number: see packaging of the product

---

**3. Intended use or uses of the construction product:**

Sealant for facade for interior and exterior application, intended for use in cold climate.

---

**4. Construction product in accordance with applicable harmonised specifications:**

EN 15651-1:2012: Type F-EXT-INT-CC: CLASS 25HM

---

**5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

OÜ KRIMELTE  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

Not relevant (see 5)

---

**7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

System 3 for the type testing / System 3 for the reaction to fire

---

**8. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

FUNDACION TECNALIA RESEARCH & INNOVATION (notified body nr. 1292), and GINGER CEBTP (notified body nr. 0074), performed the determination of the product-type and testing of the reaction to fire under system 3 and issued test reports.

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-023051

Version 1 / September 2014

**KRIMELTE**

Member of  Wolf Group



Page 2 of 2

## 9. Declared performance:

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
Reaction to fire : (EN 13501-1:2007 + A1:2010)	Class B	EN 15651-1: 2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness, as:		
• Resistance to flow	≤ 3 mm	
• Loss of volume	≤ 10 %	
• Tensile properties (i.e. at maintained extension) at -30°C (modif. EN ISO 8340)	NF	
• Tensile properties at maintained extension after water immersion (EN ISO 10590)	NF	
<b>Durability:</b>	Pass	
Conditioning method A / Tested on anodized aluminium and mortar M2 without primer		

## 10. Declaration:

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Margus Matsal

Product Manager  
13619 Tallinn, Estonia  
25/09/2014