

ETS NORD Suomi  
Pakkasraitti 4  
04360 Tuusula  
info@etsnord.fi  
myynti@etsnord.fi  
040 1842 842

**Product name:** Protective duct cover

**Article number:** TA71301300 – 250 mm  
TA71301500 – 500 mm  
TA71301750 – 750 mm  
TA713011000– 1000 mm



- Field of application:**
- In accordance with VDI 6022, tear proof, single-sided self-adhesive polyethylene film for sealing air ducts, pipes, formed parts and other ducting components
  - Protective duct cover against soiling during storage, transport and assembly
  - Dust proof
  - Particularly good adhesive properties on galvanised or stainless steel and aluminium
  - Film can be quickly removed without leaving any residue. A removal after several weeks is also possible without any problems (min 3 weeks).
  - **Please note** that the wrapped ducts shouldn't be exposed to direct sun for a longer time. Temperatures in direct sun exposition are much higher so the film will strongly stick to the steel.
  - Specifically adjusted to the requirements of ductwork

**Properties:**

Support film:	LDPE
Colour:	blue-transparent
Thickness:	0.04 – 0.05 mm
Elongation of break (%):	230
Adhesive:	Polyacrylate dispersions
Weatherproof and UV-resistant:	max. 3 months

- Processing:**
- The surfaces which are to be treated have to be dry, free of dust, oil, separating agents and other contaminants.
  - Processing temperature range (temperature of object and ambient temperature): +15°C - 45°C
  - Lift off temperature for the removal of the film (surface area temperature and ambient temperature): >+5°C
  - Use a laminating device with rubberised pressurised rollers
  - Avoid stretching the film and forming bubbles/creases when laminating
  - The film is not suitable for heavy duty deep drawing

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.

**Packaging:** Width: 250 mm, roll length 100 m, sales unit = 16 rolls  
Width: 500 mm, roll length 100 m, sales unit = 8 rolls  
Width: 750 mm, roll length 100 m, sales unit = 4 rolls  
Width: 1,000 mm, roll length 100 m, sales unit = 4 rolls

Alternative roll widths are available upon request

**Storage:** Under normal storage conditions, the rolls of film can be stored for 6 months. They should be protected from dust and moisture.

**Waste disposal:** Protective duct covers neither contain plasticisers nor heavy metals and in addition, they are fully recyclable. In adherence with official regulations, the films can be disposed of alongside domestic waste.